



SANDPIPER

Jack-up platform



Type	Combifloat C-5
Overall length	18.30 m
Breadth	12.20 m
Leg length	27.30 m
Leg diameter	30 inches
Leg section data (x4)	Bottom section 17.4 m Weight 10 t Top section 10.0 m Weight 6 t
Type of jacking system	Automated hydraulic with pilot console – 2 rams per spudwell
Operational displacement	Up to 215.28 t
Water depth including tide	15 m based on 6 m average leg penetration
Draft	0.6 m
Deck space	215 m ²
Support vessel requirements	Tug with 6-10 t bollard pull
Registration	Panama
MMSI No.	352001813
Call Sign.	HOA2854
Class certification	DNV-GL 100AS Self-elevating platform

- 12 or 24-hour operation available;
- 20' welfare/stores - air con. AIS and VHF radio, kitchen facilities, wifi internet, fully stocked workshop.
- Adjustable boarding ladder and walkway
- Hydraulic deck-mounted BS500-6M hiab crane
- Sonic, rotary and cable percussion rigs plus drilling masts can be accommodated;
- Mob boat – Ribcraft 6.4m RIB;
- Top push CPT rams complete with self-contained power pack;
- 3-phase 90kVa generator;
- 20' logging container
- Survey positioning system (can be tailored to project specification);
- Optional Wison-APB© wireline deployed CPT system.

